

60HZ Model	1800 rmp/480v 3P 4W/50HZ/0.8F				Engine specifications					Dimensions & Weight			
	PRP		STP							Openset		Silentpower	
	KVA	KW	KVA	KW	Engine Model	Fuel Cons(L/hr)	Rated output(KW)	Cylinder arrangement	Displacement (L)	Dimensions(mm)	Weight(Kg)	Dimensions(mm)	Weight(Kg)
DW-62T6	62.5	50	68.8	55.0	WP4D66E201	14.64	60	4L	4.5	1970*800*1650	1300.0	2650*1100*1900	2050
DW-94T6	93.8	75	103.1	82.5	WP4D100E201	22	90	4L	4.5	2060*900*1350	1700.0	3000*1100*1900	2550
DW-113T6	112.5	90	125.0	100.0	WP4D118E201	26	108	4L	4.5	2400*950*1700	1800.0	3200*1380*1900	2650
DW-135T6	125.0	100	137.5	110.0	WP6D132E201	30	120	6L	6.75	2400*950*1700	1800.0	3200*1380*1900	2650
DW-150T6	150.0	120	165.0	132.0	WP6D158E201	36	144	6L	6.75	2460*950*1650	1900.0	3200*1380*1900	2750
DW-188ST6	N.A	N.A	187.5	150.0	WP6D180E201	45	180※	6L	6.75	2840*1100*1940	2000.0	3500*1380*2150	2950
DW-68T6	67.5	54	75.0	60.0	BF4M2012	16.6	63	4L	4.03	1820*750*1150	980.0	2650*1100*1750	1630
DW-80T6	80.0	64	90.0	72.0	BF4M2012C	20.2	79	4L	4.03	1910*850*1300	980.0	2650*1100*1750	1630
DW-85T6	85.0	68	95.0	76.0	BF4M1013E	22.6	85	4L	4.764	2230*850*1450	1100.0	3000*1100*1900	1850
DW-110T6	100.0	80	113.0	90.0	BF4M1013EC	26.5	105	4L	4.764	2230*850*1450	1200.0	3000*1100*1900	1950
DW-114T6	114.4	91.5	143.0	114.4	BF4M1013FC	32.3	124	4L	4.764	2400*950*1550	1250.0	3200*1380*2150	2100
DW-156T6	156.3	125	174.0	140.0	BF6M1013EC	39.5	155	6L	7.146	2450*1000*1600	1250.0	3200*1380*2250	2100
DW-194T6	193.8	155	216.0	172.8	BF6M1013FCG2	47	186	6L	7.146	2510*1060*1680	1250.0	3200*1380*2250	2100
DW-215T6	215.0	172	239.0	191.2	BF6M1013FCG3	53.6	204	6L	7.146	2510*1060*1680	1300.0	3200*1380*2250	2150
DW-250T6	250.0	200	275.0	220.0	BF6M1015-LA GB	55	225	6v	11.906	2400*1520*1950	1400.0	3200*1700*2400	2250
DW-313T6	312.5	250	343.8	275.0	BF6M1015C-LA G2B	67.4	279	6v	11.906	2530*1520*1950	1500.0	3200*1700*2400	2350
DW-350T6	350.0	280	385.0	308.0	BF6M1015C-LA G3B	74	306	6v	11.906	2530*1520*1950	1650.0	3200*1700*2400	2500
DW-463T6	462.5	370	508.8	407.0	BF8M1015C-LA G1B	99.5	408	8v	15.874	2820*1820*2150	2100.0	3500*1880*2500	3100
DW-488T6	487.5	390	536.3	429.0	BF8M1015CP-LA G1B	106	429	8v	15.874	3060*1820*2150	2200.0	3800*1880*2500	3300
HM-775T6	775.0	620	852.5	682.0	TBD620L6-3A	163	690	6L	26.53	4800*1690*2200	5300.0	6058*2436*2591	7500
HM-1125T6	1125.0	900	1237.5	990.0	TBD620V8-3A	241	1016	8V	35.1	4570*1900*2600	9400.0	6058*2436*3600	12200
HM-1625T6	1625.0	1,300	1787.5	1430.0	TBD620V12-3A	341	1440	12V	50.1	4930*2200*2800	11300.0	6058*2436*3600	13300
HM-2250T6	2250.0	1,800	2475.0	1980.0	TBD620V16-3A	455	1920	16V	70.82	7320*2200*2900	18000.0	12192*2438*3600	20300