

60HZ Model	1800 rmp/480v 3P 4W /60HZ/0.8F				Engine specifications					Dimensions & Weight			
	PRP		STP		Engine Model	Fuel Cons(L/hr)	Rated output(KW)	Cylinder arrangement	Displacement (L)	Openset		Silentpower	
	KVA	KW	KVA	KW						Dimensions(mm)	Weight(Kg)	Dimensions(mm)	Weight(Kg)
DWW-68T6	67.5	54	74.3	59	DB58/64KW	16.4	64	6L	5.785	2080*800*1290	1050	3000*1100*1750	1800
DWW-105T6	95.0	76	104.5	84	D1146/96KW	24.7	96	6L	8.071	2180*800*1450	1360	3000*1100*1750	2110
DWW-131T6	131.3	105	144.4	116	D1146T/125KW	32.5	125	6L	8.071	2260*800*1450	1420	3000*1100*1750	2170
DWW-194T6	193.8	155	213.1	171	P086TI-1/174KW	50.6	174	6L	8.071	2510*950*1500	1720	3200*1380*2100	2570
DWW-228T6	227.5	182	250.3	200	P086TI/205KW	50.6	205	6L	8.071	2510*950*1500	1770	3200*1380*2100	2620
DWW-315T6	315.0	252	346.5	277	P126TI/278KW	70.3	278	6L	11.051	2780*1120*1560	2220	3500*1380*2100	3220
DWW-350T6	350.0	280	385.0	308	P126TI-II/307KW	78.5※	307	6L	11.051	2910*1120*1560	2250	3800*1380*2100	3250
DWW-409T6	408.8	327	449.6	360	P158LE-1/366KW	102.5	366	8V	14.618	2840*1400*1800	2500	4500*1880*2250	3700
DWW-450T6	450.0	360	495.0	396	P158LE/402KW	102.5	402	8V	14.618	2840*1400*1800	2540	4500*1880*2250	3740
DWW-500T6	500.0	400	550.0	440	P158LE-S/441KW	111.5	441	8V	14.618	3080*1400*1800	2600	4360*1880*2250	3800
DWW-563T6	562.5	450	618.8	495	P180LE/497KW	128.2	497	10V	18.273	3240*1400*1800	2900	4360*1880*2250	4200
DWW-594T6	593.8	475	653.1	523	P180LE-S/519KW	132.1	519	10V	18.273	3240*1400*1800	2900	4360*1880*2250	4200
DWW-625T6	625.0	500	687.5	550	P222LE-1/563KW	139.7	563	12V	21.927	3390*1400*1850	3500	5000*1880*2250	5000
DWW-681T6	681.3	545	749.4	600	P222LE/591KW	153.9	591	12V	21.927	3390*1400*1850	3500	5000*1880*2250	5000
DWW-720T6	720.0	576	792.0	634	P222LE-S/625KW	151.6	625	12V	21.927	3610*1400*1850	3500	5000*1880*2250	5000
DWW-750T6	750.0	600	800.0	640	P222FE/659KW	175.1	659	12V	21.927	3610*1400*1850	3500	5000*1880*2250	5000
DWW-871T6S	N.T	N.T	871.3	697	P222FE- II /765KW	193※	765※	12V	21.927	3610*1400*1850	3650	5000*1880*2250	5150