

50HZ Model	1500rpm/400v 3P 4W/50HZ/0.8F				Engine specifications					Dimensions & Weight			
	PRP		STP							Openset		Silentpower	
	KVA	KW	KVA	KW	Engine Model	Fuel Cons(L/hr)	Rated output(KW)	Cylinder arrangement	Displacement (L)	Dimensions(mm)	Weight(Kg)	Dimensions(mm)	Weight(Kg)
MSW-675T5	675.0	540.0	742.5	594.0	S6R2-PTA	143.0	575	L6	24.51	3700*1690*2275	5839	6060*2438*2591	9849
MSW-750T5	750.0	600.0	825.0	660.0	S6R2-PTAA	160.4	645	L6	29.96	3900*1780*2080	5935	6060*2438*2591	9935
MSW-800T5	800.0	640.0	880.0	704.0	S12A2-PTA	163.2	656	V12	33.93	4100*1725*2080	7429	6060*2438*2591	11429
MSW-938T5	937.5	750.0	1031.3	825.0	S12H-PTA	221.4	890	V12	37.11	4500*1775*2400	9190	6060*2438*2896	13190
MSW-1063T5	1062.5	850.0	1168.8	935.0	S12H-PTA	221.4	890	V12	37.11	4500*1775*2400	9190	6060*2438*2896	13190
MSW-1275T5	1275.0	1020.0	1402.5	1122.0	S12R-PTA	262.2	1080	V12	49.03	4450*2050*2335	11507	6060*2438*2896	19507
MSW-1375T5	1375.0	1100.0	1512.5	1210.0	S12R-PTA2	282.8	1165	V12	49.03	4450*2050*2335	11787	6060*2438*2896	19787
MSW-1500T5	1500.0	1200.0	1650.0	1320.0	S12R-PTAA2	310.0	1277	V12	49.03	5300*2100*2600	12219	12192*2438*3150	20219
MSW-1750T5	1750.0	1400.0	1925.0	1540.0	S16R-PTA	357.2	1450	V16	65.37	5260*2100*2425	15200	12192*2438*3150	23200
MSW-1875T5	1875.0	1500.0	2062.5	1650.0	S16R-PTA2	389.2	1580	V16	65.37	5275*2100*2875	15123	12192*2438*3600	23123
MSW-2000T5	2000.0	1600.0	2200.0	1760.0	S16R-PTAA2	414.8	1684	V16	65.37	6100*2200*2875	16128	12192*2438*3600	24128
MSW-2250T5	2250.0	1800.0	2500.0	2000.0	S16R2-PTAW	478.0	1960	V16	79.90	6420*2825*3365	18600	12939*2896*4420	24261