

50HZ Model	1500 rmp/400v 3P 4W/50HZ/0.8F				Engine specifications					Dimensions & Weight			
	PRP		STP							Openset		Silentpower	
	KVA	KW	KVA	KW	Engine Model	Fuel Cons(L/hr)	Rated output(KW)	Cylinder arrangement	Displacement (L)	Dimensions (mm)	Weight(Kg)	Dimensions (mm)	Weight(Kg)
PW-9T5	8.8	7.0	9.6	7.7	403A-11G1※	2.6	8.6	L3	1.13	1060*650*1000	500	1700*1060*1750	800
PW-9T5	8.8	7.0	9.6	7.7	403D-11G※	3.2	10.7	L3	1.13	1060*650*1000	450	1700*1060*1750	750
PW-13T5	12.5	10.0	13.8	11.0	403D-15G※	3.7	12.2	L3	1.49	1100*700*1100	500	1700*1060*1750	800
PW-13T5	12.5	10.0	13.8	11.0	403A-15G1	3.7	12.2	L3	1.49	1100*700*1100	500	1700*1060*1750	800
PW-15T5	15.0	12.0	16.5	13.2	403A-15G2※	4.1	13.6	L3	1.49	1100*700*1100	520	1700*1060*1750	820
PW-20T5	20.0	16.0	22.0	17.6	404A-22G1※	5.3	18.7	L4	2.21	1250*700*1150	630	1900*1060*1750	980
PW-20T5	20.0	16.0	22.0	17.6	404D-22G※	5.3	18.7	L4	2.21	1250*700*1150	630	1900*1060*1750	980
PW-30T5	30.0	24.0	33.0	26.4	1103A-33G	7.1	28.2	L3	3.30	1410*830*1250	850	2250*1060*1750	1250
PW-45T5	45.0	36.0	49.5	39.6	1103A-33TG1	10.7	42.2	L3	3.30	1580*830*1250	980	2400*1060*1750	1430
PW-60T5	60.0	48.0	66.0	52.8	1103A-33TG2	13.9	59.3	L3	3.30	1670*830*1250	1000	2400*1060*1750	1450
PW-65T5	65.0	52.0	71.5	57.2	1104A-44TG1※	14.8	59.6	L4	4.40	1790*830*1250	1070	2650*1100*1750	1570
PW-80T5	80.0	64.0	88.0	70.4	1104A-44TG2※	18.7	73.4	L4	4.40	1830*830*1250	1100	2650*1100*1750	1600
PW-80T5	80.0	64.0	88.0	70.4	1104C-44TAG1※	18.6	75	L4	4.40	1830*830*1250	1020	2650*1100*1750	1520
PW-93T5	90.0	72.0	99.0	79.2	1006TG1A	21.2	86.3	L6	5.99	2160*830*1250	1280	3000*1100*1900	1830
PW-100T5	100.0	80.0	110.0	88.0	1006TG2A	23.0	94.4	L6	5.99	2110*950*1400	1340	3000*1380*1900	1890
PW-100T5	100.0	80.0	110.0	88.0	1104C-44TAG2※	93.6	93.6	L4	4.40	1790*830*1250	1120	2650*1100*1750	1620
PW-135T5	135.0	108.0	148.5	118.8	1106A-70TAG1※	31.2	122	L6	7.00	2320*950*1450	1600	3200*1380*2050	2150
PW-135T5	135.0	108.0	148.5	118.8	1006TAG	31.5	128.4	L6	5.99	2310*950*1450	1420	3200*1380*2050	1970
PW-150T5	150.0	120.0	165.0	132.0	1106A-70TAG2※	34.6	135	L6	7.00	2320*950*1450	1640	3200*1380*2050	2190
PW-150T5	150.0	120.0	165.0	132.0	1006TAG2	41.0	136.8	L6	5.99	2310*950*1450	1450	3200*1380*2050	2000
PW-180T5	180.0	144.0	198.0	158.4	1106A-70TAG3※	41.2	161	L6	7.00	2380*950*1450	1700	3200*1380*2050	2250
PW-180T5	180.0	144.0	198.0	158.4	1106C-E66TAG4	40.2	158	L6	6.6	2380*950*1450	1700	3200*1380*2050	2250
PW-200T5	200.0	160.0	220.0	176.0	1106A-70TAG4※	45.8	178.9	L6	7.00	2380*950*1450	1750	3200*1380*2050	2300
PW-225T5	225.0	180.0	247.5	198.0	1306C-E87TAG4	53.0	205	L6	8.70	2480*1100*1650	1880	3500*1380*2150	2580
PW-250T5	250.0	200.0	275.0	220.0	1306C-E87TAG6	56.9	224	L6	8.70	2480*1100*1650	1900	3500*1380*2150	2600
PW-275T5	275.0	220.0	302.5	242.0	1606A-E93TAG4	54.5	239	L6	9.30	3035*1100*1650	2030	4000*1380*2150	3030
PW-300T5	300.0	240.0	330.0	264.0	1606A-E93TAG5	59.5	261	L6	9.30	3035*1100*1650	2030	4000*1380*2150	3030
PW-350T5	350.0	280.0	385.0	308.0	2206A-E13TAG2	71.0	324.2	L6	12.50	3200*1150*2000	3100	4500*1380*2250	3300
PW-400T5	400.0	320.0	440.0	352.0	2206A-E13TAG3	81.0	368.4	L6	12.50	3200*1150*2000	3230	4500*1380*2250	4430
PW-450T5	450.0	360.0	495.0	396.0	2506A-E15TAG1	95.0	412	L6	15.20	3360*1150*2000	3400	4500*1380*2250	4600
PW-500T5	500.0	400.0	550.0	440.0	2506A-E15TAG2	100.0	451	L6	15.20	3360*1150*2000	3550	4500*1380*2250	4750
PW-600T5	600.0	480.0	660.0	528.0	2806A-E18TAG1A	123.0	539.7	L6	18.13	3320*1550*2100	4130	4500*1700*2500	5030
PW-650T5	650.0	520.0	715.0	572.0	2806A-E18TAG2	132.0	584	L6	18.13	3390*1555*2100	4280	4500*1700*2500	6080
PW-750T5	750.0	600.0	825.0	660.0	4006-23TAG2A	163.0	658	L6	22.92	3760*1710*2300	4900	5000*2000*2560	6900
PW-800T5	800.0	640.0	880.0	704.0	4006-23TAG3A	175.0	705	L6	22.92	4030*1710*2300	5000	6058*2436*2591	7000
PW-1000T5	1000.0	800.0	1100.0	880.0	4008TAG2A	226.0	805	L8	30.56	4700*2050*2400	7420	6058*2436*2591	10620
PW-1258T5	1250.0	1000.0	1375.0	1100.0	4012-46TWG2A	258.0	1106	V12	45.84	4810*1780*2500	8970	12192*2438*2896	10970
PW-1505T5	1500.0	1200.0	1650.0	1320.0	4012-46TAG2A	328.0	1212	V12	45.84	4900*2160*2600	9580	12192*2438*2896	12780
PW-1505T5	1500.0	1200.0	1650.0	1320.0	4012-46TWG4A	316.0	1308	V12	45.84	4770*1980*2650	9130	12192*2438*2896	12330
PW-1710T5	1710.0	1368.0	1881.0	1504.8	4012-46TAG3A	380.6	1500	V12	45.84	5090*2160*2600	10050	12192*2438*2896	13250
PW-1850T5	1850.0	1480.0	2035.0	1628.0	4016TAG1A	383.0	1588	V16	61.12	5630*1660*3400	10050	12192*2438*3800	13250
PW-2000T5	2000.0	1600.0	2200.0	1760.0	4016-61TRG2	421.0	1744	V16	61.12	4480*1723*3400	10140	12192*2438*3800	13340
PW-2000T5	2000.0	1600.0	2200.0	1760.0	4016TAG2A	434.0	1766	V16	61.12	5630*1660*3400	10140	12192*2438*3800	13340
PW-2250T5	2250.0	1800.0	2475.0	1980.0	4016-61TRG3	473.0	1975	V16	61.12	4560*1723*3400	10400	12192*2438*3800	13600