

60HZ Model	1800 rmp/480v 3P 4W /60HZ/0.8F				Engine specifications					Dimensions & Weight			
	PRP		STP		Engine Model	Fuel Cons(L/hr)	Rated output(KW)	Cylinder arrangement	Displacement (L)	Openset		Silentpower	
	KVA	KW	KVA	KW						Dimensions(mm)	Weight(Kg)	Dimensions(mm)	Weight(Kg)
PW-11T6	11.3	9	12.4	9.9	403D-11G※	3.16	10.7	L3	1.13	1150*700*850	450	1800*900*1350	750
PW-15T6	15.0	12	16.5	13.2	403A-15G2※	5	16	L3	1.49	1200*700*1050	500	1800*900*1350	800
PW-16T6	16.3	13	17.9	14.3	403D-15G※	4.32	14.7	L3	1.496	1230*700*1050	550	1800*900*1350	850
PW-24T6	23.8	19	26.1	20.9	404D-22G※	6.2	22	L4	2.216	1350*700*1100	630	1800*900*1350	980
PW-35T6	35.0	28	38.5	30.8	404D-22TAG	8.9	33.1	L4	2.216	1500*850*1280	700	2250*1060*1750	1300
PW-63T6	62.5	50	68.8	55.0	1104D-44TG1	16.6	58	L4	4.4	1675*850*1280	1050	2250*1060*1750	1650
PW-94T6	93.8	75	103.1	82.5	1104D-E44TAG1	23.69	88	L4	4.4	1870*850*1350	1100	2650*1100*1750	1800
PW-108T6	108.8	87	119.6	95.7	1006TG1A	25.8	101.6	L6	5.99	2140*850*1250	1300	2800*1100*1750	2100
PW-112T6	112.5	90	123.8	99.0	1104D-E44TAG2	27.77	106	L4	4.4	1890*850*1400	1200	2650*1100*1950	1900
PW-120T6	120.0	96	132.0	105.6	1006TG2A	28.9	112.4	L6	5.99	2190*850*1400	1350	2800*1100*1950	2150
PW-155T6	150.0	120	165.0	132.0	1006TAG	37.6	144.2	L6	5.99	2270*850*1400	1420	3000*1100*1950	2400
PW-156T6	156.3	125	171.9	137.5	1106D-E66TAG2	37.7	144.6	L6	6.6	2300*850*1400	1600	3000*1100*1950	2600
PW-168T6	168.8	135	185.6	148.5	1106D-E66TAG3	40.1	154.4	L6	6.6	2300*850*1400	1600	3000*1100*1950	2600
PW-200T6	200.0	160	220.0	176.0	1106D-E66TAG4	48.5	185.7	L6	6.6	2460*850*1400	1700	3200*1100*1950	2800
PW-245T6	245.0	196	269.5	215.6	1306C-E87TAG4	54.4	220	L6	8.7	2460*1000*1600	1900	3200*1100*1950	3000
PW-400T6	400.0	320	440.0	352.0	2206D-E13TAG2	87	373.6	L6	12.5	2990*1120*2050	2800	3800*1380*2250	4000
PW-438T6	437.5	350	481.3	385.0	2206D-E13TAG3	94	406.5	L6	12.5	2990*1120*2050	2900	3800*1380*2250	4100
PW-500T6	500.0	400	550.0	440.0	2506D-E15TAG1	113	458	L6	15.2	3210*1100*2050	3400	4000*1380*2250	4700
PW-569T6	568.8	455	625.6	500.5	2506C-E15TAG3	121	519	L6	15.2	3210*1100*2050	3500	4000*1380*2250	4800
PW-681T6	681.3	545	749.4	599.5	2806A-E18TAG3	144	617.5	L6	18.13	3210*1540*2150	4250	4000*1700*2500	5900
PW-681T6	681.3	545	749.4	599.5	2806C-E18TAG3	145	617.5	L6	18.13	3210*1540*2150	4400	4000*1700*2500	6100
PW-750T6	750.0	600	825.0	660.0	4006-23TAG2A	176	676	L6	22.92	3590*1710*2250	4900	6058*2436*2591	6500
PW-844T6	843.8	675	928.1	742.5	4006-23TAG3A	200	759	L6	22.92	3790*1710*2250	5000	6058*2436*2591	6800
PW-884T6	883.8	707	972.1	777.7	4008TAG1	199	800	L8	30.561	4480*2050*2400	7400	6058*2436*2591	9500
PW-995T6	995.0	796	1094.5	875.6	4008TAG2	224	894	L8	30.561	4580*2050*2400	7500	6058*2436*2591	9600
PW-1251T6	1251.3	1001	1376.4	1101.1	4012-46TWG2A	266	1106	V12	45.482	4570*2000*2600	9000	12192*2438*2896	11000