

60HZ Model	1800 rmp/480v 3P 4W /60HZ/0.8F				Engine specifications					Dimensions & Weight			
	PRP		STP		Engine Model	Fuel Cons(L/hr)	Rated output(KW)	Cylinder arrangement	Displacement (L)	Openset		Silentpower	
	KVA	KW	KVA	KW						Dimensions(mm)	Weight(Kg)	Dimensions(mm)	Weight(Kg)
SW-275T6	275.0	220	300.0	240	DC09 073A 02-21	63.3	251	L5	9.3	2730*1270*1795	2305	3500*1380*2200	3650
SW-300T6	300.0	240	330.0	264	DC09 073A 02-22	68.9	273	L5	9.3	2840*1270*1795	2485	3500*1380*2200	3800
SW-325T6	325.0	260	357.5	286	DC09 073A 02-23	73.7	292	L5	9.3	2900*1270*1795	2485	3500*1380*2200	3800
SW-375T6	375.0	300	412.5	330	DC09 073A 02-24	80.83	325	L5	9.3	3000*1395*1775	2260	4360*1700*2250	4250
SW-410T6	410.0	328	450.0	360	DC13 073A 02-21	90.3	372	L6	12.7	3200*1270*1940	2790	4500*1700*2250	4375
SW-455T6	455.0	364	500.5	400	DC13 073A 02-22	96.6	410	L6	12.7	3200*1270*1940	2790	4500*1700*2250	4375
SW-500T6	500.0	400	550.0	440	DC13 073A 02-23	103.8	445	L6	12.7	3280*1270*1940	2900	4500*1700*2250	4550
SW-550T6	550.0	440	605.0	484	DC16 44A 10-27	112	481	V8	15.6	3290*1270*1940	3290	4500*1700*2250	4900
SW-625T6S	N.A	N.A	625.0	500	DC16 44A 10-27A	130※	545※	V8	15.6	3290*1270*1940	3390	4500*1700*2250	5000
SW-635T6	635.0	508	700.0	560	DC16 46A 10-29	132	555	V8	15.6	3265*1270*1940	3675	4500*1700*2250	5275
SW-650T6	650.0	520	715.0	572	DC16 072A 02-11	136.4	576	V8	16.4	3170*1320*2050	3800	4500*1700*2250	5400
SW-700T6	700.0	560	770.0	616	DC16 072A 02-12	123	619	V8	16.4	3250*1320*2050	3900	4500*1700*2250	5500
SW-728T6	727.5	582	800.3	640	DC16 072A 02-13	152	642	V8	16.4	3250*1320*2050	4000	4500*1700*2250	5600